




RESIDENTIAL AND COMMERCIAL
WINDOW AND DOOR SPECIALISTS
GATEWISE METALS

**GW100 COMMERCIAL
GRADE SERIES**




PRODUCT CATALOG

GW100 SLIDING WINDOW	01
GW100 CHAIN WINDER AWNING WINDOW	05
GW100 FIXED WINDOW	09
GW100 DOUBLE HUNG WINDOW	13
GW100 GLASS LOUVRE	17
GW100 SLIDING DOOR	21
GW100 SWING DOOR	25
GW80 BIFOLDING DOOR	29
FLYSCREEN SELECTIONS	33
GLASS SELECTIONS	34
FIXING METHOD	35
FINISHING:POWDER COATING	37
OUR SUPPLIERS	38
GW WINDOWS ORDERING FLOWS	39
PROJECTS COLLECTION	40



About

Us



Gatewise Metals P/L is one of the most experienced Suppliers of aluminium windows&doors, Our products comply with AS2047, AS1288, AGWA, WERS certificates . We specialize in providing you with creative and diverse residential and commercial window and door solutions to help you build your dream home.

Our parent company for over 35 years has provided Quality,Value & Service plus has set the benchmark in the building industry and enjoyed high reputation in the market.

Our aim is to provide the best value to the people we serve. We achieve this by providing guidance, expertise, and commitment to assist you with compliant installations. We have a continuous improvement culture that focuses on delivering a better product & service at a higher quality, quicker lead-time and at a competitive price. Our delight is to give you confidence and peace of mind.

Established in 1990, we attribute much of our success to many people we serve and dedicated business partners who have the same core principles of trust and integrity. As members of the Australian Window Association, you can be confident that our products have been tested in WERS Window Energy Rating Scheme and comply with Australian Standards AS2047 & AS1288.

We are looking forward to being of service and supplying high quality products to you!



COMPANY CERTIFICATES



AUSTRALIAN
**GLASS &
WINDOW**
ASSOCIATION

2025 CERTIFICATE OF MEMBERSHIP

THIS IS TO CERTIFY THAT

GATEWISE METALS

MEMBER NUMBER **38110**

is a current member of AGWA Limited and undertakes
to abide by the AGWA Constitution and Code of Ethics.

Dean Haritos

Chairperson

[Signature]

Executive Director & CEO



7 Ronald Ave Ryde



4 Daffodil St Eastwood



GW100 SLIDING WINDOW

Much like sliding doors, sliding windows open horizontally, by sliding along rails. Sliding windows are easy to use, low maintenance, and economical. Sliding windows also offer the possibility of having very large windows which can be easily opened without significant effort.



GW100 SLIDING WINDOW



Standard: AS2047

Design SLS/ULS:600Pa/2000Pa

Design Water Resistance:200Pa

Sound Insulation:<36DB

WERS Data: Uw Range:3.5 - 6.4

SHGC Range:0.33 - 0.60



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size:Max Height: 1800mm

Max Window Panel width: 1500mm

Maximum adaptive weight:80KG

Available glazing:Double Glazed: up to 26mm IGU

Frame dimension:Frame Depth: 105mm ;

Bottom frame Height : 45mm



Extrusion Profiles :6063-T5 with 1.6mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with
10 Years Warranty

Flynet:Fibreglass and Stainless Steel Security Mesh
Available

Fixing Method:Sub sill/head /Fin fix / face fix /Timber reveal

Hardware : China Brand & Australia Doric Available





GW100 SLIDING WINDOW



Hardware Selections

① Brand: Doric

② Origin Country: Australia

③ Model: DS6005

④ Color: Black, Silver

Feature:

The DS6005 Avon Sliding window lock has a sleek contemporary design with a large, easy to grab handle.

Hardware Selections

① Brand: Doric

② Origin Country: Australia

③ Model: DN560

④ Color: Black, Silver

Feature:

The DN560 sliding window lock is the perfect compliment for windows that demand style.





GW100 CHAIN WINDER AWNING WINDOW

As the awning window's chain winder is located on the sill, these windows can be positioned higher up along the wall to limit anyone being able to see in, whilst still allowing in all the fresh air and natural light. Alternatively, if this type of window is used in a bathroom, using an obscure glass allows you to use this window for ventilation while still getting all the benefits of the privacy glass.



GW100 AWNING WINDOW



Standard: AS2047

Design SLS/ULS:1200Pa/4000Pa

WERS Data:Uw Range:4.6 - 6.9

Sound Insulation:<38DB

Design Water Resistance:450Pa

SHGC Range:0.28 - 0.46



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size: Max Height: 2400mm, Max Window Panel width: 2400mm

Maximum adaptive weight: 100KG

Available glazing: Double Glazed: up to 26mm IGU

Frame dimension: Frame Depth: 105mm ; Bottom frame Height : 54mm




Extrusion Profiles : 6063-T5 with 2.0mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with 10 Years Warranty

Flynet: Fibreglass and Stainless Steel Security Mesh Available

Fixing Method: Sub sill/head / Fin fix / Timber reveal

Hardware : German Brand & Australia Doric Available





GW100 AWNING WINDOW



DS1 Chainwinder

① Brand: Doric

② Origin Country: Australia

③ Model: DS1

④ Color: Black, Silver

Feature:

Being the industry leader, the DS1 Chainwinder allows for easy operation and installation in a secure key lockable configuration.

DN400 Twin Chainwinder

① Brand: Doric

② Origin Country: Australia

③ Model: DN400

④ Color: Black, Silver

Feature:

The DN400 Twin Chainwinder can be pre-restricted in order to comply with the NCC and to meet the requirements of Kids Don't Fly.





GW100 FIXED WINDOW

Fixed window can help to keep your room warm in winter and cool in summer, making for effective energy saving and climate control.



GW100 FIXED WINDOW



Standard: AS2047

Design SLS/ULS:1200Pa/4000Pa

WERS Data: Uw Range:2.9~6.3

Sound Insulation:<40DB

Design Water Resistance:600Pa

SHGC Range:0.40 - 0.73



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size:Max Height: 3000mm,Max Window Panel width: 3000mm

Maximum adaptive weight: 300KG

Available glazing:Double Glazed: up to 26 IGU

Frame dimension:Frame Depth: 105mm ;Bottom frame Height : 54mm



Extrusion Profiles :6063-T5 with 2.0mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with 10 Years Warranty

Flynet:Fibreglass and Stainless Steel Security Mesh Available

Fixing Method:Sub sill/head/ Fin fix /Timber reveal

Hardware : without





GW100 FIXED WINDOW





GW100 DOUBLE HUNG WINDOW

Aluminium double hung windows offer a simple aesthetic that is ideal for a variety of different interior and exterior styles.

The minimal design conceals a spring balance operating system and internal rivets. The vertical sliding of our aluminium double hung windows allows for effortless ventilation, with equally easy cleaning and low maintenance.



GW100 DOUBLE HUNG WINDOW



Standard: AS2047

Design SLS/ULS:1000~3000pa

WERS Data: Uw Range:2.6~3.6

Sound Insulation:<38DB

Design Water Resistance:250pa

SHGC Range:0.32 - 0.65



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size:Max Height:1200,Max Window Panel width: 1500

Maximum adaptive weight:50KG

Available glazing:Double Glazed: up to 26mm IGU

Frame dimension:Frame Depth:105mm;Bottom frame Height : 65mm






Extrusion Profiles :6063-T5 with 1.6mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with 10 Years Warranty

Flynet:Fibreglass and Stainless Steel Security Mesh Available

Fixing Method:Sub sill/head /Fin fix /Timber reveal

Hardware : USA-Caldwell





GW100 DOUBLE HUNG WINDOW



Quick tilt application

① Brand: USA-Caldwell

② Origin Country: USA

③ Model: RS-TS02

④ Color: Black, White



Feature:

Pre assembled- reduce window assembly time Intergrated coil next and cover-Minimizes Contamination and Debris Robust drop in Cam-excellent structure performanceOptional friction adjuster-allows for easy field adjustment Optional Tamper lock-Limits Unintended Sash Removal

Commercial new construction

① Brand: USA-Caldwell


② Origin Country: USA

③ Model: RS-TS01

④ Color: Black, White


Feature:

High Lift Assistance-Make a heavy sash easy to operate Boosted force curve-Fits many common balance pockets AMAA Class 5 rating-balance lift 70% of sash weight Low carbon steel Rod-Rust resistance





GW100 COMMERCIAL SERIES



GW100 GLASS LOUVRE

Glass louvres are the perfect addition to any living space, and with several glass options to choose from, you can ensure the perfect fit. Durable and stylish, they strike a unique balance of effortless functionality.



GW100 GLASS LOUVRE



Standard: AS2047

Design SLS/ULS:400pa/1200pa

WERS Data: Uw Range:4.6~6.5

Sound Insulation:<28DB

Design Water Resistance:150pa

SHGC Range:0.45 - 0.76



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size: Max Height: 2700mm, Max Window Panel width: 800mm

Maximum adaptive weight: 10KG

Available glazing: Double Glazed: up to 6mm

Frame dimension: Frame Depth: 105mm ; Bottom frame Height : 50mm



Extrusion Profiles : 6063-T5 with 2.0mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with 10 Years Warranty

Flynet: Fibreglass and Stainless Steel Security Mesh Available

Fixing Method: Sub sill/head / Fin fix / Timber reveal

Hardware : CHN-MTEN





GW100 GLASS LOUVRE



RS Louvre Galleries

① Brand: China Brand

② Origin Country: China

③ Model: 6ALPP24

④ Color: Black, white

Feature:

Louvres are the ideal window solution to creating an open functional living environment. Vent, the 100% Opening Advantage Ergonomic handle design Non-Scratch UV-stabilised powder coat



GW100 SLIDING DOOR

Sliding door open horizontally, and are held up by wheels or suspended on a track, unlike standard doors which are suspended on hinges and open by turning. Sliding doors are commonly used for bathrooms and for external doors made of glass. Sliding doors save space, allow maximum light, and can create an open and spacious appearance.



GW100 SLIDING DOOR



Standard: AS2047

Design SLS/ULS:1600Pa/3000Pa

WERS Data: Uw Range:3.1 - 6.1

Sound Insulation:<36DB

Design Water Resistance:200pa

SHGC Range:0.41 - 0.67



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size:Max Height:3000mm,Max Window Panel width: 1600mm

Maximum adaptive weight:200KG

Available glazing:Double Glazed: up to 26mm IGU

Frame dimension:Frame Depth:105mm;Bottom frame Height : 45mm



Extrusion Profiles :6063-T5 with 2.0mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with 10 Years Warranty

Flynet:Fibreglass and Stainless Steel Security Mesh Available

Fixing Method:Sub sill/head /Fin fix /Timber reveal

Hardware : China Brand & Australia Doric Available





GW100 SLIDING DOOR



DS3130 Sliding Door Lock

① Brand:Doric

② Origin Country:Australia

③ Model:DS3130

④ Color:Black, Silver

Feature:

The DS3130 Timbarra Twiin Sliding Patio Door Lock was the first non-handed twin actuator system to be offered in the Australian market.

DS2400 Sliding Door Lock

① Brand:Doric

② Origin Country:Australia

③ Model:DS2400

④ Color:Black, Silver

Feature:

The DS2400 handle range has the flexibility for various configurations and handle shapes. The patio door furniture features simple snib operation as well as a clean and contemporary aesthetic, ideal for apartment and residential application.





GW100 SWING DOOR

The hinged opening door is traditionally the first option that most people consider when looking for a new or a replacement door. So much so that the hinge is not even referenced, as the majority of entrance and internal doors are hinged. Hinged doors can be left or right opening depending on your preference and space.



GW100 SWING DOOR



Standard: AS2047

Design SLS/ULS:600Pa/1400Pa

WERS Data: Uw Range:3.7 - 6.2

Sound Insulation:<36DB

Design Water Resistance:200pa

SHGC Range:0.32 - 0.57



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size:Max Height:2700mm,Max Window Panel width: 1100mm

Maximum adaptive weight:150KG

Available glazing:Double Glazed: up to 26mm IGU

Frame dimension:Frame Depth:105mm;Bottom frame Height : 26mm



Extrusion Profiles :6063-T5 with 2.0mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with 10 Years Warranty

Flynet:Fibreglass and Stainless Steel Security Mesh Available

Fixing Method:Sub sill/head /Fin fix /Timber reveal

Hardware : China Brand & Australia Doric Available





GW100 SWING DOOR



DS1400 Hinged Door Lock

① Brand:Doric

② Origin Country:Australia

③ Model:DS1400

④ Color:Black, Silver

Feature:

The DS1400 Series range is finished in Satin Black powdercoat, with the levers and escutcheon manufactured from cast aluminium. It is easy to install and suitable for hinged doors in single French & bi-fold door.

DN7300 Hinged Door Lock

① Brand:Doric

② Origin Country:Australia

③ Model:DN7300

④ Color:metallic

Feature:

The DN7300 Series is compatible for use with the Doric DN995 (23mm/30mm/38mm) Commercial narrow back-set mortice lock mechanism in a wide variety of functions that will suit all commercial locking requirements in Australia and New Zealand.





GW100 COMMERCIAL SERIES



GW80 BIFOLDING DOOR

Aluminum bifolding doors are more than just stylish – they are manufactured to last and provide durable performance. Their minimalist design aesthetic create a seamless statement in a variety of spaces, while the folding functionality opens up the possibilities to perfectly complement alfresco style dining or entertaining areas.



GW80 BIFOLDING DOOR



Standard: AS2047

Design SLS/ULS:600Pa/3000Pa

WERS Data: Uw Range:2.7 ~ 3.2

Sound Insulation:<38DB

Design Water Resistance:200pa

SHGC Range:0.36 - 0.52



GW100 COMMERCIAL SERIES

TECHNICAL SPECIFICATIONS

Available size: Max Height: 3600mm, Max Window Panel width: 900mm

Maximum adaptive weight: 200KG

Available glazing: Double Glazed: up to 32mm IGU

Frame dimension: Frame Depth: 87.5mm; Bottom frame Height : 59mm



Extrusion Profiles : 6063-T5 with 2.0mm Thickness

Powder Coating : AKZO-NOBLE Interpon Powder with 10 Years Warranty

Flynet: Fibreglass and Stainless Steel Security Mesh Available

Fixing Method: Sub sill/head / Fin fix / Timber reveal

Hardware : CHN- KSBG





GW80 BIFOLDING DOOR



Bifolding Door

① Brand: China Brand KSBG

② Origin Country: China

③ Model: KSBG-80


④ Color: Silver, Black

Feature:

automatic lock function Hardware hidden design satisfy any combination of folds Corner design with wide vision



FLYSCREEN SELECTIONS



0811 Security Screen

- | | | |
|-----------------------------|-----------------------------|--------------------|
| ① Material: SUS304 | ② Finishing: Powder coating | ③ Thickness: 0.8mm |
| ④ Weave: 11/cm ² | ⑤ Color: Black, Grey | |

0514 Security Screen

- | | | |
|-----------------------------|-----------------------------|--------------------|
| ① Material: SUS304 | ② Finishing: Powder coating | ③ Thickness: 0.5mm |
| ④ Weave: 11/cm ² | ⑤ Color: Black, Grey | |

0218 Security Screen


- | | | |
|-----------------------------|-----------------------------|----------------------|
| ① Material: SUS304 | ② Finishing: Powder coating | ③ Thickness: 0.185mm |
| ④ Weave: 18/cm ² | ⑤ Color: Black Only. | |

1511 Pet screen

- | | | |
|--|-----------------------------|----------------|
| ① Material: 30% fabric, 70%PVC coating | ② Finishing: Powder coating | |
| ④ Mesh: 360g/m ² | ⑤ Weave: 15*11 /inch | ⑥ Color: Black |



GLASS SELECTIONS



Laminated Glass


- ① Thickness: 8.76mm/10.76mm/11.14mm/12.76mm/13.14mm
- ② Treatment: tempered, Heat soaked thermally tempered
- ③ vinyl interlayer : PVB
- ④ Interlayer thickness: 0.38mm/0.76mm/1.14mm
- ⑤ Color: Ultra Clear, Clear, Obscure, tint
- ⑥ Finishing: Reflective, Spendral

Feature: Safe, Strength wind pressure, high impact resistance, reduce noise.

Single Glass

- ① Thickness: 5mm/6mm/8mm/10mm/12mm
- ② Treatment: tempered, Heat soaked thermally tempered
- ③ Color: Ultra Clear, Clear, Obscure, tint
- ④ Finishing: Reflective, Spendral

Feature: Safe, Strength wind pressure, high impact resistance




Double Glass

- ① Thickness: 6mm+12A+6mm/6mm+12A+8.76mm /6mm+9A+10.76mm
- ② Glass spacer color: Silver/black
- ③ Gas: Air/Argon
- ④ Treatment: tempered, Heat soaked thermally tempered
- ⑤ Color: Ultra Clear, Clear, Obscure, tint
- ⑥ Finishing: Reflective, Spendral

Feature: Safe, Strength wind pressure, high impact resistance, reduce noise, energy efficiency



FIXING METHOD



Sub Head, Sub Sill, Angle

Features: High water leakage resistance, simple installation (saving labor), safety, fast delivery

Wall structure suitable:

Concrete structure

Light Gauge and Hebel Structure

Double Brick Structure

Light Gauge and Brick Structure


Application: Commercial Buildings, Apartment, Townhouse, Dwellings




Sub Head



Sub Sill



Angle



Sub Head, Sub Sill, Sub Frame

Features: High water leakage resistance, simple installation (saving labor), safety, fast delivery

Wall structure suitable:

Concrete structure

Light Gauge and Hebel Structure

Double Brick Structure

Light Gauge and Brick Structure

Application: Commercial Buildings, Apartment, Townhouse, Dwellings



Sub Head




Sub Sill



Sub JOMB



FIXING METHOD



40mm Fin

Features: high water leakage resistance, simple and fast installation and safety;


Wall structure suitable:

Timber Stud and 100/150mm Hebel Structure

Brick Veneer Structure

Light Gauge and Brick Structure

Application: Townhouse, Dwellings



40mm Fin



Timber reveal + Dampcourse

Features: high water leakage resistance, simple and fast installation and safety;

Wall structure suitable:

Timber Stud and 100/150mm Hebel Structure

Brick Veneer Structure

Light Gauge and Brick Structure

Application: Townhouse, Dwellings



Timber reveal

Standard Color


Standard Color: Black/Monument/Grey/White




Smooth Black-C31122S 2 GN



Smooth Monument-GP22PC



Light Grey-C30520 S 2 GP



Smooth White-C31878 S 2 GB

Custom color



- ① Brand: Interpon
- ② Customized color: Color bond or RAL swatches
- ③ 10 years warranty Higher resistance products available either.

Features Safe, clean, economical and eco-friendly excellent performance
Meet the wide range of global coatings standards.




OUR SUPPLIERS



We are proud of having built a long term cooperation with the partners above. We are really appreciative of them giving us comprehensive advice so that we can make quality products and provide professional service for our clients. Better products will be created through the efforts from our partners, the clients and GW team.



GW WINDOWS ORDERING FLOWS





PROJECTS COLLECTION



FOLLOW US



Contact Number :

0416 223 886 (Carol)

0422 040 050 (Le)

Email: info@gatewisemetals.com.au

Web: gatewisemetals.com.au

MANUFACTURER:

Gatewise Metals Pty Ltd

Showroom & Factory

8 Pat Devlin Close Chipping Norton NSW 2170



Facebook



Instagram